



## VERIFICATION OF COMPLIANCE

No.: GPSD SHES2311021011AT

Applicant: Hangzhou Hikvision Digital Technology Co., Ltd.  
No.555 Qianmo Road, Binjiang District, Hangzhou 310052, China

Manufacturer: Hangzhou Hikvision Digital Technology Co., Ltd.  
No.555 Qianmo Road, Binjiang District, Hangzhou 310052, China

Product Name: Access Controller

Model No.: See page 2

Trade Mark: **HIKVISION**

Rating: See page 2

Protection against Electric Shock: Class III

Additional Information (if any): None

Sufficient samples of the product have been tested and found to be in conformity with

Test Standard: EN 62368-1:2014+A11:2017  
as shown in the

Test Report Number(s): SHES231102101101

This Verification of GPSD Compliance has been granted to the applicant based on the results of tests performed by Laboratory of SGS-CSTC Standards Technical Services Co., Ltd. on sample of the above-mentioned product in accordance with the provisions of the relevant specific standards and the General Product Safety Directive 2001/95/EC.

Andrew Zhai  
Technical Manager



2023-11-21

SGS-CSTC

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services which can be accessible at <https://www.sgs.com/en/terms-and-conditions>.

Member of SGS Group (Société Générale de Surveillance)

No.:

GPSD SHES2311021011AT

Other information added:

Model / Type Ref	Ratings	Model Remark
DS-K2702WX-E1(P)	Input: 12 V d.c., 6 A/Bat 12 V d.c., 5 A; PoE (802.3at, 42,5 V d.c.-57 V d.c.), 0,7 A; Output: 12 V d.c., Power: WIEGAND: 12 V d.c., 0,15 A each; LOCK POWER: 12 V d.c., 1 A; PoE Power: WIEGAND: 12 V d.c., 0,15 A each; LOCK POWER: 12 V d.c., 10 W; Class III	DC input + BAT input + PoE input + Control 2 interfaces output
DS-K2702WX-E1(P)UHK		
DS-K2702WX-E1(P)CKV		
DS-K2702WX-E1(P)UVS		
DS-K2702WX-E1(P)KVO		
DS-K2702WX-E1(P)HUN		
DS-K2704X(P)	Input: 12 V d.c., 8,5 A/Bat 12 V d.c., 7,5 A; Output: WIEGAND: 12 V d.c., 0,15 A each; LOCK POWER: 12 V d.c., 4 A; Class III	DC input + BAT input + Control 4 interfaces output
DS-K2704X(P)UHK		
DS-K2704X(P)CKV		
DS-K2704X(P)UVS		
DS-K2704X(P)KVO		
DS-K2704X(P)HUN		
DS-K2702X(P)	Input: 12 V d.c., 4,2 A/Bat 12 V d.c., 4,2 A; Output: WIEGAND: 12 V d.c., 0,15 A each; LOCK POWER: 12 V d.c., 2 A; Class III	DC input + BAT input + Control 2 interfaces output
DS-K2702X(P)UHK		
DS-K2702X(P)CKV		
DS-K2702X(P)UVS		
DS-K2702X(P)KVO		
DS-K2702X(P)HUN		
DS-K2701X(P)	Input: 12 V d.c., 3,5 A/Bat 12 V d.c., 3,5 A; Output: WIEGAND: 12 V d.c., 0,15 A each; LOCK POWER: 12 V d.c., 1 A; Class III	DC input + BAT input + Control 1 interface output
DS-K2701X(P)UHK		
DS-K2701X(P)CKV		
DS-K2701X(P)UVS		
DS-K2701X(P)KVO		
DS-K2701X(P)HUN		

Andrew Zhai  
 Technical Manager



2023-11-21

SGS-CSTC

Copyright of this verification is owned by SGS-CSTC Standards Technical Services Co., Ltd. and may not be reproduced other than in full and with the prior approval of the General Manager. This verification is subjected to the governance of the General Conditions of Services which can be accessible at <https://www.sgs.com/en/terms-and-conditions>.

Member of SGS Group (Société Générale de Surveillance)