

# KPT-23 Remote Keypad Series with Proximity Reader

Easy and Secure Access  
at Your Fingertips



- A 16-button backlit keypad
- Optional RFID key fob or NFC tag

KPT-23 Series is an intelligent two-way wireless remote keypad providing easy-to-use, on-premises security system control for enhanced flexibility and convenience. For enhanced flexibility and convenience, KPT-23 series can integrate with RFID key fobs or NFC tags for secure quick access without entering pin codes manually.

Safeguarded by tamper protection, the KPT-23 Series is protected from being opened or removed from the mounting surface. To provide additional peace of mind and safety, this keypad series features dual key function that can activate panic, fire or medical alarm at one press.

Featuring power saving design, the KPT-23 Series consumes no power when it is in stand-by mode, and further offers models with extended battery life. Sleek and stylish, the KPT-23 Series blends with any décor, making it an ideal choice for any application.

## Features

- Enables user to arm/disarm the security system by simply swiping RFID key fobs or NFC tags
- Integrates up to 30 RFID key fobs or NFC tags
- Dual key function to trigger panic, fire or medical alarms
- Extended battery life (optional)
- Power conservation feature that consumes power only when in operation
- Complied with CE requirements
- A 16-button backlit keypad for easy night time visibility
- Tamper protection against unauthorized removal
- Low battery detection
- Extensive RF communication range, faster signal transmission
- Sleek, modern design with easy wall-mounted installation

## Specifications

### KPT-23-F1 / KPT-23N-F1

Frequency	868MHz / 433MHz
Power Source	3V, CR2 Lithium battery x 1
Battery Life	3.5 years*
Key Fob Reader Protocol	ISO 15693
NFC Tag Dimensions	45 mm x 25 mm
NFC Protocol	ISO 14443A
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	80 x 116 x 20.5 mm

## KPT-23 Remote Keypad Series with Proximity Reader

### KPT-23-EL-F1 / KPT-23N-EL-F1

Frequency	868 MHz / 433 MHz
Power Source	3V, EL123AP Lithium battery x 1
Battery Life	6.5 years*
Key Fob Reader Protocol	ISO 15693
NFC Tag Dimensions	45 mm x 25 mm
NFC Protocol	ISO 14443A
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	80 mm x 116 mm x 20.5 mm

### Ordering Information

---

<b>KPT-23-F1</b>	Remote Keypad and RFID Key Fob
<b>KPT-23-EL-F1</b>	Remote Keypad and RFID Key Fob, with extended battery life
<b>KPT-23N-F1</b>	Remote Keypad and NFC Tag
<b>KPT-23N-EL-F1</b>	Remote Keypad and NFC Tag, with extended battery life