

DC-15SL Door Contact

An Ideal Choice to Guard Your
Doors and Windows



- Long Battery life
- Extensive RF range
- Serves as a Universal Transmitter
- Tamper Protection

DC-15SL is a wireless Door / Window Contact designed to monitor the opening and closing of doors and windows. DC-15SL is multi-functional, with a built-in extension terminal which allows an existing wired sensor to be connected, and also serves as a universal transmitter.

DC-15SL has a compact and low-profile design allowing it to seamlessly fit into any home décor, and ideal for both residential and commercial installations and usage. DC-15SL adopts the latest RF technologies to deliver long RF range, fast signal transmissions, and super long battery life.

DC-15SL alerts the system control unit to any irregular activities and sends low battery signals as well as regular supervision signals to check system integrity, for a peace of mind and a safer home.

Features

- Monitors the opening and closing of doors, windows, cabinets and drawers
- Built-in Extension Terminal for enhanced flexibility to add wired detectors
- Doubles as a universal transmitter
- Randomized Supervision signals to check system integrity
- LED serves as a fault and test mode indicator
- Wireless for easy installation
- Extensive RF communication range & faster signal transmission
- Tamper protection
- Low battery detection
- Compliant with CE requirement
- EN 50131 Grade 2, Class II Certified

Specifications

Frequency	F1 868 MHz / F1 433MHz
Power Source	3V, CR2 Lithium battery x1
Battery Life	9.3 years*
Operating Temperature	-10°C to 45°C (14°F to 113°F)
Operating Humidity	Up to 85% non-condensing
Dimensions	107mm x 32mm x 22mm

* Note: The actual battery life may vary with product settings, usage patterns and operating environment.