

FI/CQR983-GAS GAS DETECTOR with RELAY OUTPUT



- Advanced detection and discrimination algorithms
- Easy Installation and maintenance
- Sleek low-profile housing
- 4 Wire
- Comes complete with base
- SMD circuit board design
- Magnet test feature
- Compatible with all Firebrand Conventional panels

This Conventional Gas Detector is effective for detecting any buildup of natural gas in your residence, and is engineered to perform the following features:-

1. Easy to install. Allowing connection to any conventional fire panel.
2. Monitors any accidental leaks of natural gas in a continuous manner.
3. Emits a loud alarm (>70dB) when it detects a buildup of natural gas.
4. Continuously self-tests its operative functions.

TECHNICAL SPECIFICATIONS

Type of gas Sensed :	Natural (Methane)
Voltage DC :	12/24 VDC
Power Consumption :	2 W
Operating Temperature :	-10°C~50°C
Sensitivity:	Less than 1/4 LEL of Natural Gas
Alarm Contact :	Form A/Auto Reset



FireBrand



CQR Fire & Security
125 Pasture Road, Moreton, Wirral, CH46 4TH, UK

Sales: 0151 606 1000 Tech: 0151 606 6311 www.cqr.co.uk info@cqr.co.uk

