

ATS1236

32 zones 433Mhz wireless receiver DGP

Increasing zone capacity

The ATS1236 wireless receiver adds wireless capabilities to the Advisor Advanced range of panels.

The wireless DGP supports most of the legacy 433 MHz 63-bit transmitters as well as the new generation of 433 MHz LoNa transmitters of which the wireless communication is fully encrypted, avoiding unauthorized interference. Up to 32 wireless sensors and up to 16 keyfobs can be learned in.

The ATS1236 wireless receiver provides two wired zone inputs and one programmable relay output.

Installation and programming

The wireless DGP needs to be installed outside the panel housing in order to assure a maximum wireless range. The 433MHz wireless solution will monitor the status and presence of each wireless device and will respond in case of an RF jamming condition.

The ATS1236 wireless receiver can be programmed from the keypad as well as from the downloader. The firmware of the module is remotely upgradeable.



Details

- Adds wireless capabilities to Advisor Advanced
- Two wired zone inputs
- One programmable SPDT Form C relay output
- Supports legacy 63-bit 433 MHz and new LoNa 433 MHz transmitters
- Learn-mode technology
- Removable terminals
- EN50131-1/EN50131-3/EN50131-6 Grade 2 Class II (pending) INCERT (pending)
- Firmware upgradeable

ATS1236

32 zones 433Mhz wireless receiver DGP

Technical specifications

General

| | |
|-----------------|-----------------------------------|
| Expander type | Wireless expander |
| Product line | Advisor Advanced |
| Connection type | Databus connection |
| Compatibility | Advisor Advanced MR 4.2 or higher |

Inputs

| | |
|-----------------------|-------------------------------|
| Total | 32 |
| No. of wireless zones | 32 wireless sensors (one way) |
| Onboard | 2 wired |

Outputs

| | |
|-----------------|-------------------|
| Onboard | 1 |
| Type of outputs | SPDT Form C relay |

Wireless

| | |
|---------------------|------------------------------|
| Operating frequency | 433 MHz legacy, 433 MHz LoNa |
|---------------------|------------------------------|

Electrical

| | |
|---------------------|--------------------------------|
| Operating voltage | 12 VDC via bus |
| Current consumption | typical 47 mA maximum 51 mA |

Physical

| | |
|---------------------|------------------|
| Physical dimensions | 155 x 95 x 26 mm |
| Net weight | 0.160 kg |
| Colour | White |
| Material | ABS plastic |

Environmental

| | |
|-----------------------|-------------------------------------|
| Operating temperature | -10°C to +55°C |
| Relative humidity | 90% relative humidity noncondensing |
| Environment | Indoor |

Standards & regulation

| | |
|------------|----------------------------------|
| Compliance | CE, RoHS |
| Standards | EN50131 Grade 2 & INCERT pending |

