#### **Product data sheet**



## AS510

### Outdoor ABS siren with single red beacon



#### **Details**

- · Attractive high quality shaped housing
- $\bullet\,$  Double piezo sounder with 114 dB @ 1m sound output
- · Vertical or horizontal mounting
- Fully potted electronics
- Strobe flash light
- Selectable comfort LED indication
- Pry-off and opening tamper detection
- Fully compliant with CE, BS and IS requirements
- Self detection of cable cutting or tampering
- Installer Friendly
- Hold-off polarity selection
- Independently hold-off for both beacon and siren
- A choice of cut off time
- Selectable tamper configuration

# AS510

## Outdoor ABS siren with single red beacon

### **Technical specifications**

General	
Grupo de accesorios	Sirena
Tipo	Sirena exterior
1100	Silena exterior
Eléctrico	
Voltaje de	10 to 14.5 V
funcionamiento	
Consumo de corriente	350 mA
Físico	
Dimensiones físicas	210 x 300 x 55 mm
Peso neto	841 g
Medioambiental	
Temperatura de	-25 to 55 °C
funcionamiento	
Material	
	ABS (3 mm)
Sounder	
	Double piezo
PCB protection	
POB protection	Fully potted
	· any potted
Tamper & pry-off	Vec
	Yes
Power supply	
	10.0 to 14.5 VDC
Standby current (typical)	
	40 mA (with NiCd battery)
	20 mA (without battery)
Operating current	(typical)
	350 mA
Sound output	
	114 dB
Eroquoney	
Frequency	0.5 to 3 kHz
	0.5 to 5 KHZ
Operating tempera	
	-25 to +55°C
Flash frequency	
	50 to 60 flashes/min
Cut-off timer	
	3 min, 5 min, 10 min, 20 min
Comfort LED	
	Yes
	103

Dimensions (W x H x D)	
	210 x 300 x 55 mm
Low voltage detec	tion
	Yes
Metal inner cover	
	Optional
Optional self-activ	ating battery
	10.8 V / 280 mAh

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

