

# SC-22-0200-0001-99

## SmartCell Dual Smoke/Heat Detector and Combined Sounder

### Overview

---

The SmartCell Dual Smoke / Heat Detector With Sounder is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include dual smoke and/or heat detection, integrated sounder with 32 tones, bidirectional 868 MHz communication, fire indication LED and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



### Details

---

- Fully wireless
- Quick and easy to install
- Compact profile
- Flexible detection; smoke and/or heat
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

# SC-22-0200-0001-99

## SmartCell Dual Smoke/Heat Detector and Combined Sounder

### Technical specifications

---

#### General

---

Wireless frequency	868 MHz
Compatibility	SmartCell

---

#### Sounder

---

Output level	89 dB(A) at 1 m max.
Output level adjustment	High or low
Selectable tones	32

---

#### Physical

---

Physical dimensions	110 x 58 mm (Ø x D)
Net weight	0.2 kg
Colour	White
Mounting type	Ceiling mount
Batteries	3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)

---

#### Environmental

---

Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries) -10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indoor
IP rating	IP21C

---

#### Standards & regulation

---

Compliance	CE
Certification	CPR
Standards	EN54-3 EN54-5 EN54-7 EN54-13 EN54-25

---

#### Detection

---

Sensitivity	Smoke: Normal, Normal+AVF. Heat: 58 °C, static (A2S), 58 °C rate of rise (A2R), 72 °C static (BS), 72 °C rate of rise (BR)
-------------	--

---

