Product data sheet



SC-32-0120-0001-99

SmartCell Red Sounder and Wall-Beacon (VAD White Flash)

Overview

The SmartCell Sounder Beacon is quick and easy to install and offers individual addressing at the SmartCell Control Panel.

Features include part 23 VAD, 32 sounder tones, bidirectional 868 MHz communication and an anti-tamper locking mechanism.

This device is third party certified and compatible with the full SmartCell product range.



Details

- Fully wireless
- Quick and easy to install
- Includes part 23 VAD
- 32 sounder tones
- Unique design
- Inbuilt locking mechanism

SC-32-0120-0001-99

SmartCell Red Sounder and Wall-Beacon (VAD White Flash)

Technical specifications

General	
Wireless frequency	868 MHz
Sounder	
Output level	95 dB(A) at 1 m max.
Output level adjustment	High or low
Selectable tones	32
VAD	
Colour	white flash
Rating	W-2.4-6
Flash frequency	0.5 Hz (1 flash, every 2 seconds)
Physical	
Physical dimensions	110 x 77 mm (Ø x D)
Net weight	0.2 kg
Colour	Red
Mounting type	Wall mount
Mounting position	Wall
Batteries	3 x ER14505M 3.6 V lithium thionyl chloride batteries (Fanso or Titus)
Environmental	
Operating temperature	-10 to +55°C
Storage temperature	-10 to +30°C (with batteries) -10 to +55°C (without batteries)
Relative humidity	95% noncondensing max.
Environment	Indoor
IP rating	IP21C
Standards & regula	ation
Compliancy	CE
Certification	CPR
Standards	EN54-3
	EN54-13
	EN54-23 EN54-25
	ENJ4-ZJ

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

