

Micro Smoke Alarm

SK-20 is the smallest domestic smoke alarm in the world, this stylish smoke alarm operated by a 3V lithium battery for 10 year lifetime.

SK-20 smoke alarm utilizes photoelectric detection technology to sense smoke from different fires. Unit have a sensing chamber which uses a beam of light and a light sensor. Smoke particles entering the chamber change the amount of light that reaches the sensor. The alarm sounds when the smoke density reaches a preset level. The smoke alarm is equipped a self-diagnostic and checking feature to ensure correct operation through its service life.

The device builds the buzzer as a test button on the front cover, however if false alarms occur, the button can be used to silence the sound for 10 minutes.

The batteries is sealed in the detector, No need to replace. After 10 years of powered operation, an audible warning will occur indicating that the detector should be replaced. In case of the horn will pulse on three times for 10ms separately by 330ms every 43 seconds to warn to replace the detector. When battery come to the end of life, the smoke alarm will release short chirps to warn from low batteries. The detector ***It is strongly recommended to replace the detector immediately when the low battery warning begins.***

Features:

- Photoelectric sensor for ultimate protection.
- Big Test/Silence button at front cover for more convenient user interaction.
- 10 year lithium battery – no battery changes for ever.
- Install simply and quickly using screws (included) or almost instantly with unique 3M VHB adhesive tape.
- Test: button for testing smoke alarm's correct functioning when push the button more than 0.5 seconds.
- Silence function to silence false alarms and temporally desensitizing smoke alarm, just press and release at once.
- **Low Battery warning or The Chamber test fail warning:** If either the low battery test or the chamber test fails, the horn will beep 10ms every 43 seconds until the failing condition passes. If two consecutive chamber test fails, the horn will pulse on three times for 10ms, separated by 330ms every 43 seconds, Each of the two supervisory test audible indicators is separated by approximately 20 seconds.
- **Low battery hush:** If a low battery condition exists, the horn will be silenced for 8 hours after pressing the test button.
- End of Life Indicator: After 10 years of powered operation, an audible warning will occur indicating that the detector should be replaced.
- Local Alarm Memory: the feature allow easy identification of any unit that had previously been in a Local Alarm condition.
- Compliant with EN14604:2005.

Technical Information

Model	SK-20-XX-YY-ZZ (*)
Power	One 3V lithium battery
Sound Level	85 dB at 3 meters
Quiescent current	< 3uA @2.9V
Operation temperature	0°C – 45°C
Humidity max.(RH)	93%
Adhesive holding temp	-35°C – +93°C
Dimension	50.8 mm dia. x 42.5 mm height
Weight	54 g
Warranty	5 years limited

(*) Model code XX represents color variation number
YY represents marking language
ZZ represents manual language

Available models

Model Code	Color Number (XX)	Marking Language (YY)	User Manual (ZZ)
SK-20	01 White	EN English	english
SK-20	02 Off White	FR French	French/english
SK-20	03 Light Grey	DE German	German/english
SK-20	04 Grey	RU Russian	Russian/english
SK-20	05 Pink	ES Spanish	Spanish/english
SK-20	06 Blue		
SK-20	07 Dark		
SK-20	08 Tan		
SK-20	09 Chrome		
SK-20	10 Matt Chrome		
SK-20	11 Golden		
SK-20	12 Matt Golden		

Appearances:

