


## Magnetic Contacts Range

Full range of contacts at [www.cqr.co.uk](http://www.cqr.co.uk)


**FC508 MULTI** **FC508/WH or BR/MULTI/G2/EN**



2

- Body 20(dia) x 30mm, Face plate 22 x 33mm
- 4 Terminals
- Selectable resistors (A, B, D, E, I)
- Microswitch tamper
- Can be fitted in normal double pole configuration
- Can be used on double doors
- Operating gap - 9mm

**FC508 MULTI** **FC508/WH or BR/MULTI/G3/EN**




3

- Body 20(dia) x 30mm, Face Plate 22 x 33mm
- 4 Terminals
- Selectable resistors (A, B, D, E, I)
- Microswitch tamper
- Can be fitted in normal double Pole configuration
- Can be used on double doors
- Operating gap 4mm
- Magnetic immunity

FLUSH


**SC517 MULTI** **SC517/WH or BR/MULTI/G2/EN**



2

- 65 x 13.5 x 13mm
- 4 Terminals
- Selectable resistors (A, B, D, E, I)
- Microswitch tamper
- Can be fitted in normal double pole configuration
- Can be used on double doors
- Available white or brown
- Operating gap - 15mm

**SC517 MULTI** **SC517/WH or BR/MULTI/G3/EN**



3

- 65 x 13.5 x 13mm
- 4 Terminals
- Selectable resistors (A, B, D, E, I)
- Microswitch tamper
- Can be fitted in normal double Pole configuration
- Can be used on double doors
- Available white or brown
- Operating gap - 10mm
- Magnetic detection

SURFACE CONTACTS


**SC570 MULTI** **SC570/WH or BR/MULTI**



2

- 85 x 25 x 20mm
- 6 Terminals
- Selectable resistors (A, B, D, E, F, H, I)
- Microswitch and wall tamper
- Operating gap - 27mm


**SC570 MULTI** **SC570/WH or BR/MD/MULTI/G3**



3

- 85 x 25 x 20mm
- 6 Terminals
- Selectable resistors (A, B, D, E, F, H, I)
- Microswitch and wall tamper
- Operating gap - 10mm
- Magnetic detection


**GP001** **GP001/AB/G2**



2

- Heavy duty angled contact
- Operating gap: 50 mm
- Size: 80 x 15 x 27 mm
- High quality alloy finish
- Pre-restored (A, B)
- 45cm Armoured cable lengths
- Other resistor value available - see resistor guide for type

**GP001** **GP001/AB/G3**




3

- Heavy duty angled aluminium contact
- Operating gap: 20 mm
- Size: 80 x 15 x 27 mm
- High quality alloy finish
- Pre-restored (A, B)
- 45cm Armoured cable lengths
- Magnetic detection
- Other resistor value available - see resistor guide for type

HEAVY DUTY CONTACTS

**RS002** **RS002/ALI/G2/AB**



2

- Heavy duty roller shutter
- Operating Gap: 50 mm
- Size: 175 x 50 x 15 mm
- High quality alloy finish
- Pre-restored (A, B)
- 45cm & 1m Armoured cable lengths
- Other resistor value available - see resistor guide for type

**RS007** **RS007/G3/AB**



3

- Heavy duty roller shutter
- Operating gap: 20 mm
- Size: 175 x 50 x 15 mm
- High quality alloy finish
- Selectable (A, B)
- Optional floor tamper
- Locating mechanism to aid alignment
- 45cm & 1m Armoured cable lengths
- Other resistor value available - see resistor guide for type

### Resistor Table Guide

Type	Resistor Guide	Switch	Tamper
A	Honeywell, Microtech (Galaxy)	1K Ohms	1K Ohms
B	Scantronic, Cooper, Pyronix PCX, Texecom, Castle-Care Tec G3+	4K7 Ohms	2K2 Ohms
C	Guardall (Network 1 configuration) Two wire only	8K2 Ohms	8K2 Ohms
D	DSC	5K6 Ohms	5K6 Ohms
E	Gardtec	6K8 Ohms	4K7 Ohms

Type	Resistor Guide	Switch	Tamper
F	Bosch, DA Abacus	8K2 Ohms	3K9 Ohms
G	Castle Care-Tec	13K Ohms	1K Ohms
H	Europlex, MDT	2K2 Ohms	2K2 Ohms
I	Pyronix Matrix, GE / Aritech, HKC	4K7 Ohms	4K7 Ohms
J	Texecom	22K Ohms	10K Ohms



Independently Certified to EN50131


1 Grade 1 2 Grade 2 3 Grade 3

## Other Magnetic Contacts

Full range of contacts at [www.cqr.co.uk](http://www.cqr.co.uk)

### FLUSH CONTACTS

**FC503** **FC503/WH or BR/G2**



- 9.5(dia) x 25mm
- 4 Core pre wired
- 15mm Operating gap
- Double pole or pre-resistor - see resistor guide for type

2

**FC505** **FC505/WH or BR**



- Quick fit flush contact
- Body 19(dia) x 15 - Face plate 35 x 22mm
- 5 Terminal
- Operating gap - 23mm

1

**SC570** **SC570/WH or BR/EN**




INDEPENDENTLY CERTIFIED

- SC570/WH or BR
- 85 x 25 x 20mm
- 6 Terminals
- Microswitch and wall tamper
- Operating gap - 27mm

2

**SC570** **SC570/WH or BR/MD/G3/EN**



INDEPENDENTLY CERTIFIED

- SC570/WH or BR
- 85 x 25 x 20mm
- 6 Terminals
- Microswitch and wall tamper
- Operating gap - 10mm
- Magnetic detection

3

### SURFACE CONTACTS

**SC517** **SC517/WH or BR**



- 65 x 13.5 x 13mm
- 5 Terminals
- Operating gap - 20mm

1

**SC517** **SC517/WH or BR/G2**



- 65 x 13.5 x 13mm
- 5 Terminals
- Operating gap - 20mm
- Microswitch tamper

2


**SC513** **SC513/WH or BR/4C**



- SC513/WH or BR/4C
- 65 x 13.5 x 13mm
- Pre-wired
- Operating gap - 20
- Pre-resistor - see resistor guide for type

2

**SURFACE CONTACT SPACERS**



- 5mm Spacer
- SC570/SPACER/WH for SC570 contacts
- SC51X/SPACER/WH for SC517 / SC513 contacts
- Packs of 10 sets (10 reed and 10 magnets)
- Available in white

2

### HEAVY DUTY CONTACTS

**RS002** **RS002/ALI**



- Heavy duty roller shutter
- Operating gap: 50 mm
- Double pole
- Size: 175 x 50 x 15 mm
- High quality alloy finish
- 1 & 2 Reed versions available
- 45cm & 1m Armoured cable lengths
- Also available as pre-resistor - see resistor guide for type

2

**GP001** **GP001/G2**



- Heavy duty angled contact
- Double pole configuration
- Sealed to prevent tampering
- Operating gap: 50 mm
- Size: 80 x 15 x 27 mm

2