Product data sheet



RF-4041-07-2

2-way key fob LoNa

This 4-button 2-way keyfob, using the latest LoNa technology, allows the end-user to arm, disarm or partially arm their system without having to memorize access codes or race to beat entry or exit delays.

Each button press will be indicated by a blinking LED and the acknowledgement coming from the receiver will also trigger the LED on the keyfob.

In case the system is not ready to arm, or in case the end-user is outof-range of the receiver, this will also be visible on the keyfob when pressing a button. Even a system in alarm, will be indicated when performing a button press.

It offers one additional programmable buttons which can be used e.g. to turn on and off lights before entering the premises, activate an automated garage door, etc.

It can also be used to send a panic alarm by pressing the lock and unlock buttons simultaneously, or to trigger an auxiliary alarm by pressing the "1" and "2" button simultaneously.

This variant can be used in the ZeroWire and XGen eco-systems.



Details

- Using LoNa technology
- Compact, robust, premium design
- · LED confirmation of sent and received messages
- Out-of-range LED indication
- 1 programmable button
- Panic and Auxiliary alarm functionality available
- 5 years of battery life (based on usage)
- EN & Incert security approvals

RF-4041-07-2

2-way key fob LoNa

Technical specifications

General	
Accessory group	KeyFob
Electrical	
Compatibility	Interlogix LoNa transceicers (e.g. ZeroWire, XGen)
Wireless operating frequency	433.65 MHz
Wireless power output	-9 dBm EIRP
Battery type / life	3V lithium CR2032 / 5 years
Physical	
Physical dimensions	32 x 13 x 63 mm
Net weight	42.5 g
Environmental	
Operating temperature	0° to 49°C
Relative humidity	5 to 95% noncondensing
Standards & regula	ation
Compliancy	CE
Standards	EN Grade II & Incert

As a company of innovation, UTC Fire & Security reserves the right to change product specifications without notice. For the latest product specifications, visit UTC Fire & Security online or contact your sales representative.

