

# ZPR868-CM

## ZPR868-CM ZITON PROTOCOL 868MHZ - RADIO CLUSTER COMMUNICATOR (RCC), MAINS POWERED

### General

---

The ZPR868-CM is a mains powered wireless cluster communicator for interfacing Ziton wireless 868 MHz fire alarm devices into a ZP fire alarm system. It enables these wireless devices to be controlled directly from the ZP7 compatible CIE, and provides a seamless interface between wireless devices and the CIE.

### System design

---

A cluster communicator comprises of a radio transceiver capable of communicating with up to 31 wireless devices. Every cluster communicator communicates directly to a ZPR868-H hub or, should direct communication not be possible, via another cluster communicator (with up to 4 hops) to the hub. This allows for full meshed networked wireless systems with multiple redundant wireless communication parts as well as longer wireless communication ranges when that is required on large sites.

### Seamless addition of wireless devices

---

Every wireless device controlled through a cluster communicator has its own unique address with which the main fire alarm control panel communicates with it, providing the same system capabilities as directly wired devices. A full range of wireless detection and alarm devices is available, including multi-sensors capable of dual sensing heat and smoke, smoke only or heat only configurations, manual call points, notification devices (sounders & beacons) as well as input/output units.

### Full flexibility

---

Wireless devices are featured in many fire detection and alarm systems, specified where the installation of hard wiring would be difficult or impossible to complete, decorative finishes to the interior of the protected building preclude wiring runs or where the time scales to complete installation are minimal. Cluster communicators allow the system designer full flexibility in selecting the locations of wireless devices anywhere in the system, or even allow all the filed devices in system to be wireless, up to 508 devices per CIE (or 127 devices per loop).



### Details

---

- Mains supply with battery backup
- 2-Way communication with up to 31 wireless devices
- Diversity transceivers allow maximum operational range
- Variable power output
- ETSI 300-220 approved
- EN54-4, 18, 25 complaint and CPR certified

# ZPR868-CM

## ZPR868-CM ZITON PROTOCOL 868MHZ - RADIO CLUSTER COMMUNICATOR (RCC), MAINS POWERED

### Technical specifications

#### Electrical

Operating voltage 100 to 230 VAC

#### General

Wireless frequency 868 MHz

#### Physical

Physical dimensions 270 x 205 x 75 mm

Net weight 1.8 kg

Colour Grey (Pantone 428c)

#### Environmental

Operating temperature -10 to +50°C

Storage temperature -20 to +60°C

Relative humidity 0 to 95% noncondensing

Environment Indoor

IP rating IP54

#### Standards & regulation

Certification EN54-18, EN54-25

#### Compatibility

All ZP addressable systems

#### Application

Surface mount, indoors

#### Temperature range

Operating -10°C to +50°C

Storage -20°C to +60°C

#### Relative humidity (noncondensing)

0% to 95%

#### IP Rating

IP54

#### Operating voltage

220 to 240 VAC

#### Operating current

50 mA

#### Battery backup

Batteries 1 x 6V 4Ah

Standby time 72 h

#### Operating frequency

868 MHz

#### Output transmitter power

Variable 0-14 dBm

#### Construction

Plastic box

#### Colour

Pantone 428c Cool grey

#### Dimensions (h x w x d)

270 x 205 x 75 mm

#### Weight

1.8 kg

#### Approvals

EN54-4, 18, 25

